

IMPORTANT PRECONFIGURATION FOR IP CONSOLE

Enable Java on the web browser.

The remote client computer must have installed both:

- a web browser (such as Microsoft Internet Explorer, Mozilla Firefox, and Netscape Navigator)
- 2. a **Java** Virtual Machine (version 1.4 or higher)

JAVA Update for IP KVM

Due to the latest update from Java security, some users may receive a "**JAVA Block**" message, like this:



while accessing the remote console over IP.

If so, please download the latest IP KVM firmware from this link:

REMOTE CLIENT COMPUTER SETUP

Firmware Update Steps

- 1. Download the latest IP KVM firmware from the link: http://www.raloy.com/support/downloads/aust-i11-150608.bin
- 2. Login to the IP KVM.
- 3. Click Update Firmware.
- **4.** Click **Browse** to select the firmware file.
- 5. Click Upload.

6. Click Update.



Firmware Update	
Current version:	04.02.00 (Build 6302) / H1-AUST- 130104
New version:	04.02.00 (Build 6302) / 111-AUST- 158608
(Upthie)	Direard
This may take some minutes. Pl while the update is in progress device will be ren	ease do NOT power of the device I After a successful update, the set automatically.

7. After the firmware has been updated, IP KVM will reset automatically.

Firmware updated succ	essfully.	
The device will be rese	t in a few seconds.	
Notice	Very should be endowed with endowed at the local same in t	
	Tau incure de automaticany representatione to the login page in 1	

8. After one minute, you will be redirected to the *Login* page and requested to login again.

http://www.raloy.com/support/downloads/aust-i11-150608.bin

RALOY-TS-IP-v01 LAST UPDATED: 13 MAY 2016