

RWX119 - 19" Widescreen Console Drawer



Features & Benefits

- 19" widescreen High-Contrast LCD - 1440 x 900 Max. Res.
- 2nd Generation, cutting-edge, modern design fits into only 1U of rack space - optional 2-post mounting available.
- Simple to install, configure, and operate for easy, at-the-rack access of all your rack-based servers.
- Sharp image rendering and video performance allow for high-quality user experiences.
- Supports Windows, Linux, Mac, and other operating Systems
- USB and PS2 interface with included 6 foot console cable (PS/2 support by request).
- UL, cUL, CE, FCC, & CCC Certified
- PC, SUN or MAC keyboard layout, and audio support.
- Industry-leading 2 year warranty, extendable up to 5 years.

Modular Options

- Integrated KVM switch capability - 8 to 32 Port; 1 to 4 Users (local / extender / over-IP)
- Mouse: Touchpad or Trackball
- Keyboard available in 13 languages
- DC power options: 12V / 24V / 48V / 110V / 125V
- Audio Options: 2.5mm / Speaker / Composite (BNC)
- Video Options: VGA / DVI / HDMI (HDCP) / SDI / S-Video

19" Modular Monitor Keyboard Drawer



The second generation Raloy RWX119 state-of-the-art modular rack console offers a space saving, streamlined approach to your rack environment by integrating your monitor, keyboard, mouse and optional KVM in a single 1U rack unit. Raloy RWX119 rack console features a 19" Widescreen LCD, full 104 key keyboard and touchpad or trackball mouse. Access your servers with a streamlined, highly customizable Raloy rack console drawer. Integrate a modular KVM switch to control multiple servers from a single unit.



FC

CE



REACH



Integrated KVM Switch Options

| Cat6 KVM | Local | Extended | IP | 8-Port | 16-Port | 32-Port |
|-----------------|-------|----------|----|--------------------|--------------------|--------------------|
| | 1 | 0 | 0 | RWX119 - CATx10008 | RWX119 - CATx10016 | RWX119 - CATx10032 |
| | 1 | 0 | 0 | RWX119 - CATx11008 | RWX119 - CATx11016 | RWX119 - CATx11032 |
| | 1 | 0 | 1 | RWX119 - CATx10108 | RWX119 - CATx10116 | RWX119 - CATx10132 |
| | 1 | 1 | 1 | - | RWX119 - CATx31116 | RWX119 - CATx31132 |
| | 1 | 1 | 2 | - | RWX119 - CATx41216 | RWX119 - CATx41232 |
| | 1 | 1 | 0 | - | RWX119 - CATx21016 | RWX119 - CATx21032 |
| | 1 | 2 | 0 | - | RWX119 - CATx32016 | RWX119 - CATx32032 |
| | 1 | 3 | 0 | - | RWX119 - CATx43016 | RWX119 - CATx43032 |

Cat6 KVM Dongles: RDG-100SD (DVI-USB) / RDG-100H (HDMI-USB) / RDG-100P (DP-USB) / RDG-100S (VGA-USB) / RDG-100 (VGA-PS2)

| VGA KVM | Local | Extended | IP | 8-Port | 16-Port | 32-Port |
|----------------|-------|----------|----|-------------------|-------------------|---------|
| | 1 | 0 | 0 | RWX119 - KVM10008 | RWX119 - KVM10016 | - |
| | 1 | 1 | 0 | RWX119 - KVM11008 | RWX119 - KVM11016 | - |
| | 1 | 0 | 1 | RWX119 - KVM10108 | RWX119 - KVM10116 | - |
| | 1 | 1 | 1 | RWX119 - KVM31108 | RWX119 - KVM31116 | - |
| | 1 | 1 | 2 | RWX119 - KVM41208 | RWX119 - KVM41216 | - |
| | 1 | 1 | 0 | RWX119 - KVM21008 | RWX119 - KVM21016 | - |
| | 1 | 2 | 0 | RWX119 - KVM32008 | RWX119 - KVM32016 | - |
| | 1 | 3 | 0 | RWX119 - KVM43008 | RWX119 - KVM43016 | - |

| VGA Hub KVM | Local | Extended | IP | 8-Port | 16-Port | 32-Port |
|--------------------|-------|----------|----|--------------------|--------------------|---------|
| | 1 | 0 | 0 | RWX119 - HKVM10008 | RWX119 - HKVM10016 | - |
| | 1 | 1 | 0 | RWX119 - HKVM11008 | RWX119 - HKVM11016 | - |
| | 1 | 0 | 1 | RWX119 - HKVM10108 | RWX119 - HKVM10116 | - |

DB-15 VGA KVM Cables: RCB-6 (6 ft.) / RCB-10 (10 ft.) / RCB-15 (15 ft.)

| DVI KVM | Local | Extended | IP | 12-Port | - |
|----------------|-------|----------|----|--------------------|---|
| | 1 | 0 | 0 | RWX119 - DVIKVM112 | - |

DVI-D KVM Cables: RCI-6 (6ft.) / RCI-15 (15 ft.)



Dependable, integrated KVM switches for quick, efficient at-the-rack access of your critical servers.

| Model | RWX119 | RWX119 with Integrated KVM |
|--------------------------------------|--|---|
| Product Dimensions (HxWxD) | 1.73 x 17.4 x 18.1 in (44 x 442 x 460 mm) | 1.73 x 17.4 x 22.8 in (44 x 442 x 579.1 mm) |
| Package Dimensions (HxWxD) | 5.5 x 23.2 x 30.2 in (140 x 590 x 768 mm) | 5.5 x 23.4 x 30.2 in (140 x 595 x 768 mm) |
| Net Weight | 25.3 lb (11.5 kg) | 28 lb (12.5 kg) |
| Mounting Depth | 18 .1 in. (min) to 29.5 in. (max) (460 to 749.3 mm) | 23.5 in. (min) to 34.5 in. (max) (596.9 to 876.3 mm) |
| KVM Cable (included) | 1 x 6 ft Combo Cable (VGA, USB) | 8-Port: 8 x KVM Cable; 16 & 32-Port: 16x KVM Cable |
| LCD Panel / Video & Audio | | |
| Display Size | 19-inch Widescreen TFT color LCD | |
| Max Resolution (dots x lines) | 1440 x 900 | |
| Backlight Type | LED | |
| Brightness (nits) | 300 | |
| Contrast Ratio (typ.) | 1000:1 | |
| Color | 16.7 M | |
| Viewing Angle (H/V) | 160° x 160° | |
| Standard Video Input | VGA | |
| Optional Video Input | HDMI, DVI, Composite (BNC), S-Video | HDMI, DVI, DisplayPort, VGA |
| Plug & Play | VESA EDID 1.3 | |
| Audio | Optional Built-in Dual Stereo Speakers 2W x 2 | |
| Power | | |
| Supply Range | Auto-sensing 100 to 240VAC, 50 / 60Hz | |
| Keyboard | | |
| Keyboard / Mouse | 104-key Notepad Keyboard / Glidepoint Touchpad | |
| Keyboard Layout | Windows (standard), MAC , SUN | |
| Keyboard Languages | United States (standard), United Kingdom, Germany, France, Spain, Norway, Italy, Russia, Switzerland, Netherlands, Portugal, China, Japan, Korea, Arabia, Turkey | |
| Environmental Specifications | | |
| MTBF (hrs) | 50,000 | |
| Operation Temperature | 32 to 131°F (0 to 55°C) | |
| Storage Temperature | -4 to 140°F (-20 to 60°C) | |
| Operating Humidity | 20~90%, non-condensing | |



Access | Integrate | Consolidate